OPACIMETER FOR DIESEL ENGINES



OPA-300

Its small, compact size and 12 V d.c power supply mean it can be used as a portable tool in situations where this is necessary, held by its comfortable, ergonomic handle.

GUARANTEED **MODULARITY**

Like other tools of the line, the OPA-300 opacimeter can be integrated in the different BRAIN BEE emissions control configurations, providing the end user with his own control station to meet his every requirement. It can also be integrated in existing stations (on a Brain Bee trolley) demonstrating that restyling will not affect the performance of stations of those already working with Brain Bee tools.

TECHNICAL FEATURES

| LIGHT SOURCE | GREEN LED | С |
|--|--------------------------------------|---|
| LIGHT RECEIVER | PHOTODIODE | Ō |
| MEASUREMENT CHAMBER PRESSURE CONTROL | AUTOMATIC | R |
| STABILISING OF MEASURING CHAMBER AT 90°C | YES | F |
| GLASSES CLEANING SYSTEM AUTOMATIC CONTROL | AUTOMATIC | |
| AUTOZERO | AUTOMATIC | |
| HEATING TIME TO 20 °C | 10 MINUTES | |
| RPM AND TEMPERATURE RECEPTION | VIA CABLE OR RADIO | |
| CONNECTIONS | RS 232 SERIAL; RS 485 NETWORK SERIAL | |
| POWER SUPPLY | 12 VDC TYP (11-15VDC) | |
| POWER CONSUMPTION | 1A DC, 5A DC WITH HEATING ON | |
| OPERATING TEMPERATURE | 0 ÷ 40 °C | |
| DIMENSIONS | 360 X 280 X 288 MM | |
| WEIGHT | 5 KG | |

MEASURING FIELDS

| OPACITY 0 ÷ 99.9 OPACITY 0 ÷ 9.99 REV COUNTER 300 ÷ 9990 OIL TEMP 20 ÷ 150 FUME TEMP 20 ÷ 400 | M-1 REVS/MIN °C | RES. 0.1 RES. 0.01 RES. 10 RES. 1 RES. 1 RES. 1 |
|---|-----------------------|--|
|---|-----------------------|--|

HOMOLOGATIONS APPROVAL IN THE FOLLOWING COUNTRIES: ITALY, MOROCCO, NETHERLANDS, SERBIA, RUSSIA



Brain Bee S.p.A. Tel. +39.0521.954411 Fax +39.0521.954490 www.brainbee.com - contact@brainbee.com